



## 3DVF-15S



### specifications

---

|                          |  |
|--------------------------|--|
| <b>Screen Size</b>       | 15.26 inch [337.92 X 190.08 mm]  |
| <b>3D Type</b>           | Circular Glasses   |
| <b>Screen ratio</b>      | 16:9   |
| <b>Panel Type</b>        | TN TFT color LCD   |
| <b>3D Format</b>         | Side by side , Frame Sequential(3D Function Automatic Selection)   |
| <b>Mirror Processing</b> | Horizontal, Vertical Hardware based real time  |
| <b>Brightness</b>        | 250 cd/m2  |
| <b>Resolution</b>        | 2D : 1280 X 720<br>3D : 1280 X 360 (Left Image - Odd Number Field)<br>1280 X 360 (Right Image - Even Number Field) |
| <b>Display Color</b>     | 16.2 Million   |
| <b>Pixel Pitch</b>       | 0.264 mm   |
| <b>Signal Support</b>    | SMPTE 292M<br>1080 / 24P, 30P, 60i<br>720 / 30P, 60P   |
| <b>OSD Control</b>       | 2D/3D, 720p, 1080i, Left, Right, LR, Frame,<br>H Mirror, V Mirror, PA, Power                                       |
| <b>Input(Left/Right)</b> | HD-SDI x 2   |
| <b>Output(Stereo)</b>    | HD-SDI x 1   |
| <b>Connector</b>         | BNC female   |
| <b>Dimension(WxLxH)</b>  | 470 x 155 x 405 mm(W*L*H)  |
| <b>Weight</b>            | 10.8 kg  |
| <b>Power</b>             | DC 12V 3A (MAX) / 2P DIN   |
| <b>Accessories</b>       | Power Cable, Adaptor   |

---